



FALCON RIDGE

3510-1 Port Jacksonville Pkwy, Jacksonville, FL 32226
606-845-2227

Instructions for Installation and Care of
John Deere Gator HPX-XUV Mini Cab Enclosure w/ Folding Lexan Windshield
JD-XUV-MC03

Notice: Do not smoke inside the cab or expose the enclosure to direct flames. Product is Flammable.

1. Be sure to read these instructions thoroughly before opening and installing the enclosure. The installation is best done when the temperature is 70 degrees F or warmer.
2. Carefully open the carton and unroll the enclosure on a large flat surface that is clean and free of dirt or other material that may soil or scratch the windows of the enclosure.
3. Check over the parts included in the carton with the parts list shown below:

adhesive Velcro strips	4 each	10" long
adhesive Velcro strips	2 each	6" long
adhesive Velcro strip	1 each	21" long
enclosure	1 each	
4. Loosely fit the enclosure into position. Clean the roll cage and apply the two 6" adhesive Velcro strips at the top corners of the roll cage to match the sewn-in double-sided Velcro straps on the enclosure. Attach the double-sided straps to the adhesive strips on the roll cage. Raise the bed, clean the attachment area thoroughly and attach the 21" adhesive Velcro strip along the metal piece at the bottom and attach the Velcro sewn into the rear of the cab.
5. Next apply the four 10" adhesive Velcro strips down the rear tube to match the Velcro tabs sewn into the enclosure, and attach.

Cleaning and Storage Recommendations:

1. Before removing the enclosure for storage, make sure it is clean and dry, to prevent soiling the textile and scratching the clear vinyl windows. Clean with a soft rag or sponge using a mild liquid detergent soap and warm water solution. Let the enclosure dry thoroughly before attempting to roll for storage.
2. It is important that the enclosure be rolled up for storage rather than folding. Folding will cause undesirable creasing of both the enclosure textile and the clear vinyl windows. Carefully roll up the enclosure similar to the way it was when it was packed at the factory. Put the rolled enclosure back into the carton for storage at a normal room temperature. It is best not to expose the enclosure to either extreme hot or cold temperatures when storing.
3. A special cleaner/conditioner is available from Falcon Ridge that will greatly increase the service life of the cab enclosure. If needed, additional hook and loop sets are available, as well as other spare parts and hardware. Contact Falcon Ridge for information.
4. Transporting or trailering your UTV with the enclosure installed is not generally recommended. It is best to remove the enclosure before transporting your UTV.

Thank You For Your Purchase!