

3510-1 Port Jacksonville Pkwy, Jacksonville, FL 32226 800-213-7981

## <u>Instructions for Installation and Care of</u> <u>John Deere Gator HPX-XUV Rear Window Enclosure</u>

ID-XIJV-RW01

Notice: Do not smoke inside the cab or expose the enclosure to direct flames. Product is Flammable.

- 1. Be sure to read these instructions thoroughly before opening and installing the rear window enclosure. The installation is best done when the temperature is 70 degrees F. or warmer. If installed outside and in the cold weather, warming the adhesive Velcro strips inside just before installation is recommended.
- 2. Carefully open the carton and unroll the enclosure on a large flat surface that is clean and free of dirt or other material that may soil or scratch the clear vinyl.
- 3. It is necessary to raise the dump bed prior to installation.
- 4. Check over the parts included in the carton with the parts list shown below:

2" Adhesive Velcro strips	14 each	3" long
2" Adhesive Velcro strip	1 each	20" long
2" Adhesive Velcro strip	1 each	25" long
enclosure 1 each	ì	

5. Clean the roll cage tubes of any dirt. Begin by placing the 25" adhesive Velcro strip at the center of the top roll cage tube. Attach the corresponding Velcro tab sewn into the top of the enclosure to the adhesive strip and then repeat at the bottom of the enclosure. Apply the corresponding adhesive Velcro strips to the roll cage downtubes one by one and attach when finished. The four 6" strips will wrap around the tubes at the top, where the sewn-in Velcro double-sided strips are located. The next one down will be the 10" strips; apply them to match the locations of the sewn-in Velcro in the enclosure. Repeat with the 5" strips at the bottom. Ensure the enclosure is centered across the rear of the vehicle before final attachment.

### **Cleaning and Storage Recommendations:**

- 1. Before removing the enclosure for storage, make sure it is clean and dry, to prevent soiling the textile and scratching the clear vinyl windows. Clean with a soft rag or sponge using a mild liquid detergent soap and warm water solution. Let the enclosure dry thoroughly before attempting to roll for storage.
- 2. It is important that the enclosure be rolled up for storage rather than folding. Folding will cause undesirable creasing of both the enclosure textile and the clear vinyl windows. Carefully roll up the enclosure similar to the way it was when it was packed at the factory. Put the rolled enclosure back into the carton for storage at a normal room temperature. It is best not to expose the enclosure to either extreme hot or cold temperatures when storing.
- 3. A special cleaner/conditioner is available from Falcon Ridge that will greatly increase the service life of the cab enclosure. If needed, additional hook and loop sets are available, as well as other spare parts and hardware. Contact Falcon Ridge for information.
- 4. Transporting or trailering your UTV with the enclosure installed is not generally recommended. It is best to remove the enclosure before transporting your UTV.

Thank you for your purchase!

## **Falcon Ridge**

# 3510-1 Port Jacksonville Pkwy, Jacksonville, FL 32226 Phone: 800-213-7981 or 606-748-5136

If for any reason you choose to return this product it must be returned within 30 days from date item is received. YouMUST package the product exactly as it was originally packaged from the factory to get a full refund for the product! The vinyl windows should never be folded when packaging in the box or for storage purposes. Lay all the windows on top of each other with the canvas folded in between and the paper (if available) on both sides of the windows.

All returned products will be inspected upon arrival at the production facility and must be in unused, factory new condition to receive refund - a 20% restocking fee will apply.

If ordered from Falcon Ridge please call at 606-845-2227 to gain a return authorization number, use our preferred shipping carrier (UPS) to return the item (unless the item is defective, you are responsible for paying the shipping to return the item.) Any returns submitted to Falcon Ridge without a return authorization number will be charged a 20% restocking fee. If ordered from one of Falcon Ridge many distributors', you must first call them and see what their return policy is. Once your item reaches our production facility, our customer satisfaction team will inspect your item to ensure unused, factory new condition. NOTE: All Lexan windshields must be returned with the original protective film intacked and not removed. Do NOT REMOVE if you have any intentions of returning the item. Refund/ replacement on lexan windshields will only be processed on items with original protective film or if the windshield is defective.

Items must be properly packaged in the original shipping carton to protect them during transit and ensure your returned item arrives back factory fresh, and in new resalable condition (any returned items that have been used, altered or damaged in any way will not be subject for a refund.) All contents including instruction manuals, accessories, hardware, Velcro, etc. must be included in your return shipment. Only items in OEM factory new condition will be approved. Once returned items are received, credit will be issued to the original credit card/payment method used for the purchase. Outbound shipping and return shipping cost will not be refunded. Please allow 4 to 6 weeks for your refund to be processed.



#### To The Owner of this Product:

Thank you for purchasing one of our Falcon Ridge Enclosures &/or Windshields! Below are the terms under which your product is covered under our manufacturer's warranty.

30 Day Warranty which includes and is not limited to replacing the enclosure and/or windshield due to defect of the product. Please refer to the return policy in this case for more information. 1 Year Warranty includes any defect in material or workmanship within this time frame we will gladly correct the problem or replace the enclosure &/or windshield. Upon submitting for the correction or replacement we will need to receive pictures of the defect in material or workmanship along with the receipt from the date of purchase.