



FALCON RIDGE

3510-1 Port Jacksonville Pkwy, Jacksonville, FL 32226

800-213-7981

Instructions for Installation and Care of Yamaha Rhino Lexan Windshield

YA-RHINO-WD02

NOTICE: Please check contents of package for any damage and make sure all parts fit correctly and you are happy with the product before removing protective film. Once the film is removed you cannot return the product for a full refund.

1. Be sure to read these instructions thoroughly before opening and installing the Yamaha Rhino Lexan Windshield.
2. Check over the parts included in the cartons with the parts list shown below:

| | |
|---------------------------|--------|
| 1 3/4" Loom Clamps | 6 each |
| 1" Stainless Steels Bolts | 6 each |
| Stainless Steel Washers | 6 each |
| Thumb Nuts | 6 each |
| 54" Rubber Gasket | 1 each |
| Lexan Windshield | 1 each |

3. Start by pulling it out of the box, find a clean area to lay it down, and install the hardware. Begin by peeling off the protective film. Next take the 54" piece of rubber gasket and starting at one end firmly place along entire bottom edge of the Windshield.
4. Now the Windshield is ready to be installed. With the help of a friend, place the Windshield on the Rhino, setting it up onto the hood.
5. Where the slots are cut into the windshield wrap a clamp around the roll cage and insert a bolt through both holes from the inside out. Place a washer on the bolt before putting the bolt through the windshield, then place another washer over the bolt on the outside of the windshield and finally screw the thumb nut on the bolt and tighten. You may need a Phillips screwdriver to hold the bolt while tightening the thumb nut.
6. Now you are ready to take it out and enjoy. To clean the windshield, always clean using a liquid of some sort to decrease the chance of scratches. We recommend using micro fiber cloths that are readily available at any dollar store. Any window cleaner will work fine; just remember to use a soft clean rag or micro-fiber cloth to clean it.